

GOODWAY REFINING, LLC
POST OFFICE DRAWER 649
BREWTON, ALABAMA 36427

BUSINESS OFFICE:
315 BELLEVILLE AVENUE
BREWTON, ALABAMA 36426
TELEPHONE 251-867-5413
FAX 251-867-5427

PLANT SITE:
4745 ROSS ROAD
ATMORE, ALABAMA 36502
TELEPHONE 251-294-5660
FAX 251-294-5658

Technical Data Sheet
Ultra-Clear K-1 Kerosene

General Information

Goodway Ultra-Clear Kerosene (K-1) is a near colorless special low sulfur refined petroleum distillate suitable for use in kerosene burner applications. It has a mild characteristic petroleum odor.

Toxicity

Prolonged and/or repeated inhalation of vapors may cause damage to the central nervous system and prolonged and repeated skin contact will cause irritation. Contact with the eyes will cause immediate irritation. Ingestion may be lethal.

Shipping and Handling

Kerosene is a flammable hydrocarbon liquid. Keep away from ignition sources. Keep containers closed and clearly labeled. Tank cars and trucks should bear D.O.T. placards that comply with all regulations. The UN number for Kerosene is UN-1223.

Ultra-Clear K-1 Kerosene Properties and General Specifications

Physical Properties	Test Method	Results	K-1 Specs
Sulfur Content	D-4294	.0396	.040
Gravity, API	D-287	46.1	
Doctor Test	D-4952	Neg.	
Copper Corrosion	D-130	2	3
Flash Point, F	D-93	112	100 min
Color	D-156	+26	+16
Distillation, F	D-86		
10% volume recovered, max		330	400
Final boiling point, max		470	572
Specific Gravity		.795	
WT (ppg)		6.622	