

MATERIAL SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF PRODUCT

TRADE NAME: PRODUCT NUMBER: WHMIS CLASS: DESCRIPTION: PRODUCT USE: TRANSPORT:

HMIS CODE:

SUPPLIER:

VPI Cove Base Adhesive #600 VPI 36001/36004/36006 – (3600 = Product, x = size) NOT CONTROLLED ACRYLIC WALL BASE ADHESIVE WALL BASE COVERINGS ADHESIVE DOT Information: NON HAZARDOUS MATERIAL Proper Shipping Name: Adhesives (0) FIRE (0) REACTIVITY HEALTH (0)SPECIFIC (0)0:Minimal 1:Light 2:Moderate 3: High 4: Dangerous

VPI Corporation 3123 South 9th Street P.O. Box 451 Sheboygan, WI 53082-0451 Phone: (800) 874-4240 **EMERGENCY PHONE NUMBER:** CHEMTREC (800) 424-9300

SECTION 2: HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	OSHA PEL	ACGIH TLV	Other Limits	%
NONE				

SECTION 3: PHYSICAL PROPERTIES

APPEARANCE AND ODOR:	Off white paste with mild sweet odor.
BOILING POINT (°C):	100° C/212° F
SPECIFIC GRAVITY (H ₂ 0=1):	1.31
VAPOR DENSITY (Air=1):	> 1
MELTING POINT (°C):	N/A
EVAPORATION RATE:	< 1
SOLUBILITY IN WATER (%):	Soluble.
VOLATILE MATTER (% Vol.):	N/D
VAPOUR PRESSURE (mm of Hg):	N/A
PH:	N/D

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE: IF YES, IN WHICH CONDITIONS:	YES()	NO (x)			
FLASH POINT (°C):	N/A				
METHOD:	N/D				
AUTO-IGNITION TEMPERATURE (°	C): N/A				
FLAMMABLE LIMITS (% VOL.IN AIR):					
LOWER LIMIT:	N/D	UPPER LIMIT:	N/D		
EXTINGUISHING MEDIA:	WILL NOT SU	PPORT COMBUSTION			
	WATER SPRAY	Y ()	WATER FOG	()	
	CARBON DIOX	KIDE ()	FOAM	()	
	DRY CHEMICA	AL ()	OTHERS	()	
SPECIAL FIRE FIGHTING PROCEDU	JRES:				
	N/A				
UNUSUAL FIRE AND EXPLOSION HAZARDS:					
	N/A				

SECTION 5: REACTIVITY DATA

STABILITY:	UNSTABLE	()	STABLE	(x)	
CONDITIONS TO AVOID:	None				
HAZARDOUS POLYMERIZATION:	MAY OCCUR	()	WILL NOT OC	CUR	(x)
CONDITIONS TO AVOID:	None known.				
INCOMPATIBILITY (materials to avoid): Oxidizing agents and caustics.					
	WATER	()	BASE	()	
	OXIDIZING AGENTS	()	ACID	()	
	CORROSIVE	()	OTHERS	()	

HAZARDOUS DECOMPOSITION PRODUCTS:

Oxides of carbon if co-burned with flammable materials.

SECTION 6: PREVENTIVE MEASURES

VENTILATION:	Local exhaust ventilation. Special: open doors and windows to create cross ventilation during use and until adhesive dries.
RESPIRATORY PROTECTION:	None required with adequate ventilation.
EYE PROTECTION:	Safety glasses.
HAND PROTECTION:	Impervious gloves.
OTHER PROTECTIVE EQUIPMENT:	None.
HANDLING:	Practice good personal hygiene.
STORAGE:	Keep container closed when not in use. Store in a cool, well-ventilated place out
	of direct sunlight and away from incompatible materials. Follow all MSDS sheet and label warnings even after container is emptied.

SECTION 7: SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

ST ILLLD:	
	Scrape up excess and place in DOT approved container for disposal. Clean area
	with soapy water.
WASTE DISPOSAL METHOD:	Dispose of in accordance with local, state and federal environmental regulations.

SECTION 8: HEALTH HAZARD DATA

ABSORPTION ROUTE:	SKIN	()	EYES	()
	INHALATION	()	INGESTION	()
EFFECTS OF OVEREXPOSURE:	N/D			
SKIN:	N/D			
EYES:	N/D			
INHALATION:	N/D			
INGESTION:	N/A			
CARCINOGENIC:	N/A			
TERATOGENIC:	N/D			
MUTAGENIC:	N/D			

SECTION 9: FIRST AID PROCEDURES

SKIN: EYES:

INHALATION: INGESTION:

Wash affected skin with soap and water. Flush eyes with water for at least 15 minutes while holding eyelids open. Contact a physician. Move to fresh air, and aid in breathing if necessary. DO NOT INDUCE VOMITING. Contact a physician or a poison control center immediately.

SECTION 10: PREPARATION INFORMATION

REVISION DATE: 1/7/09

VPI Corporation has compiled the information and recommendations contained in this Material Safety

Data Sheet from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No warranty, guaranty or representation is made as to the correctness or sufficiency of the information. The user of this product must decide for himself what safety measures are necessary to safely use this product, either alone or in combination with other products.

N/A: Not applicable N/D: Not determined

Not established N/E:



VPI Corporation, 3123 S.9th Street, PO Box 451, Sheboygan, Wisconsin 53082-0451 U.S.A. Phone: (920) 458-4664 - Fax: (920) 458-1368 - Customer Service: (800) 874-4240 Email: floor@vpiflooring.com Website: www.vpiflooring.com